

## The AD-1 System: Distributing high quality audio from a central source to up to 20 remote locations



AD-1 TX Transmitter



AD-1 RX Receiver

### The AD-1 System (one transmitter and up to 20 receivers):

- ▶ Features a high rate of hum and noise rejection
- ▶ Prevents leakage between locations
- ▶ Uses high-level balanced line drivers
- ▶ Accepts normal "line level" inputs
- ▶ Can be "daisy-chained" for easy and fast installation
- ▶ Controls output levels at each end
- ▶ Is surface-mountable (optional rack panels available)
- ▶ Provides stereo outputs for auditoriums and a separate mono output for the lobby
- ▶ Receivers employ custom-designed transformers for full isolation

## **SPECIFICATIONS**

### **Power Requirements:**

Transmitter: 120v ac 50/60 Hz  
(220v ac version available)

Receiver: Passive

Frequency Response: 30 to 15 kHz

Separation: 70 dB or better

Distortion: .02% THD

### **Connectors:**

Power: IEC connector

Transmitter audio inputs: Terminal strip/RCA

Receiver audio outputs: Terminal strip

### **Mounting:**

Surface mount

(Rack mount, 1 unit panel adaptor available)

## **ORDER INFORMATION**

Transmitter	AD-1TX (one required for up to 20 receivers)
Receiver	AD-1RX
Rack panel mount kit	AD-1PNL